



2.5 ml SemiMicro Cuvette, Square, UV Grade PMMA



Product Highlights

- UV grade PMMA for accuracy throughout the UV/Vis range 280 to 800 nm
- Cuvettes supplied in polystyrene rack with lid for safe storage.

Product Applications

E1412-4451 is ideal for fluorometry and nephelometry

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab (UK) LTD
5 Tanners Drive
MK14 5BU Milton Keynes
Email: infoline@starlab.co.uk



General Data

Art. No.	E1412-4250
Volume	2.5 ml
Pack Size	500 Pcs. (5 Packs × 100 Pcs.)
Material	UV grade PMMA

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab (UK) LTD
5 Tanners Drive
MK14 5BU Milton Keynes
Email: infoline@starlab.co.uk



More informations about 2.5 ml SemiMicro Cuvette, Square, UV Grade PMMA

Disposable [cuvettes](#) suitable for use with most open spectrophotometers. Provides optimum transmission level on the whole visible spectral. The material used avoids any possible measurement interference. High reliability is assured, with maximum absorption variation at: +/- 1 %.

Light beam width: for 10 mm. The two sides not crossed by the light beam are ribbed to an easy identification of the [cuvette](#) position inside the spectrophotometer measurement chamber, resulting in an easy positioning and removal.