



# 12x75 Graduated Tube, Polystyrene



#### **Product Highlights**

- Graduated at 1.0 ml, 2.5 ml and 4.0 ml
- Centrifugation rate: 7000 x g (PS)
- Temperature use: -100°C0to0700°C (PS tubes with cap)
- Caps available separately

### **Product Applications**

Sample preparation
Centrifugation
Sample storage
Preparation of master mixes and buffers

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab (UK) LTD 5 Tanners Drive MK14 5BU Milton Keynes Email: infoline@starlab.co.uk







### **General Data**

Art. No.	E1412-6200
Pack Size	2,000 Tubes (2 Bag × 1000 Tubes)
Dimensions (W × D × H)	1.2 cm × 1.2 cm × 7.5 cm
Dimensions (W × D)	1.2 cm × 1.2 cm
External width	1.2 cm
Sterile	No
Material	Polystyrene
Max. temp.	80 °C
Temperature range	-50 to 80 °C
Min. temp.	-50 °C
g-Force max.	7.000 x g

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab (UK) LTD

5 Tanners Drive MK14 5BU Milton Keynes Email: infoline@starlab.co.uk







# More informations about 12x75 Graduated Tube, Polystyrene

Polystyrene tubes graduated at 1.0 ml, 2.5 ml and 4.0 ml. Leakproof push-on polyethylene cap (available separately) with a ribbed plug to clamp firmly on the tube.

Centrifugation rate: 7000 x g (PS). Temperature use: -10 $\square$ °C $\square$ to $\square$ 70 $\square$ °C (with cap).

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab (UK) LTD

5 Tanners Drive MK14 5BU Milton Keynes Email: infoline@starlab.co.uk







### **All Variations**

PRODUCT NAME		PACKAGING SIZE	ART. NO.
	12x75 Graduated Tube, Polystyrene Material: Polystyrene  Create PDF Data Sheet	2,000 Tubes (2 Bag × 1000 Tubes)	E1412-6200
	12x75 Graduated Tube, Polypropylene  Material: Polypropylene  Create PDF Data Sheet	2,000 Tubes (2 Bag × 1000 Tubes)	E1412-6201
	Caps for 12x75 Graduated Tubes Material: Polyethylene  Create PDF Data Sheet	2,000 Pcs. (1 Bag × 2000 Pcs.)	E1412-6300

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.



5 Tanners Drive MK14 5BU Milton Keynes Email: infoline@starlab.co.uk

