



## 12x75 Graduated Tube, Polystyrene



### Product Highlights

- Graduated at 1.0 ml, 2.5 ml and 4.0 ml
- Centrifugation rate: 7000 x g (PS)
- Temperature use: -10°C to 70°C (PS tubes with cap)
- Caps available separately

## Product Applications

Sample preparation

Centrifugation

Sample storage

Preparation of master mixes and buffers

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

**Starlab (UK) LTD**  
5 Tanners Drive  
MK14 5BU Milton Keynes  
Email: [info@starlab.co.uk](mailto:info@starlab.co.uk)



## General Data

Art. No.	E1412-6200
Material	Polystyrene
g-Force max.	7.000 x g
Pack Size	2,000 Tubes (2 Bag x 1000 Tubes)
Sterile	No
Temperature range	-50 to 80 °C
External width	1.2 cm
Max. temp.	80 °C
Dimensions (W x D x H)	1.2 cm x 1.2 cm x 7.5 cm
Dimensions (W x D)	1.2 cm x 1.2 cm

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

**Starlab (UK) LTD**  
5 Tanners Drive  
MK14 5BU Milton Keynes  
Email: [info@starlab.co.uk](mailto:info@starlab.co.uk)



## More informations about 12x75 Graduated Tube, Polystyrene

Polystyrene tubes graduated at 1.0 ml, 2.5 ml and 4.0 ml. Leakproof push-on polyethylene cap (available separately) with a ribbed plug to clamp firmly on the tube.







Centrifugation rate: 7000 x g (PS). Temperature use: -10°C to 70°C (with cap).

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

**Starlab (UK) LTD**  
5 Tanners Drive  
MK14 5BU Milton Keynes  
Email: [info@starlab.co.uk](mailto:info@starlab.co.uk)



## All Variations

PRODUCT NAME	PACKAGING SIZE	ART. NO.
 <a href="#">12x75 Graduated Tube, Polystyrene</a> <b>Material:</b> Polystyrene  <a href="#">Create PDF Data Sheet</a>	2,000 Tubes (2 Bag × 1000 Tubes)	E1412-6200
 <a href="#">12x75 Graduated Tube, Polypropylene</a> <b>Material:</b> Polypropylene  <a href="#">Create PDF Data Sheet</a>	2,000 Tubes (2 Bag × 1000 Tubes)	E1412-6201
 <a href="#">Caps for 12x75 Graduated Tubes</a> <b>Material:</b> Polyethylene  <a href="#">Create PDF Data Sheet</a>	2,000 Pcs. (1 Bag × 2000 Pcs.)	E1412-6300

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

**Starlab (UK) LTD**  
5 Tanners Drive  
MK14 5BU Milton Keynes  
Email: [info@starlab.co.uk](mailto:info@starlab.co.uk)