



ErgoOne® FAST Pipette Controller



Product Highlights

- Intuitive, pressure-responsive speed control
- Provides fast pipetting with maximum precision
- Low operating forces
- Lightweight and ergonomically designed for fatiguefree pipetting
- Use with all plastic or glass serological pipettes (1.0 ___100 ml)
- 2-year warranty

Product Applications

Transfer of liquid volumes from 0.10to0100 ml Serial dispensing of aliquots of different volumes Resuspension of bacteria or cell pellets and nucleic acid precipitates

Aspiration of cell layer from, e.g., Ficoll[®] gradient Phase extraction and removal of lower phases

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.







General Data

Art. No.	S7166-0010	
Pack Size	1 Piece (1 Box × 1 Piece)	
Weight	160 g (with battery)	
Autoclavable	No (yes: pipette adapter and aspirating cone)	
Volume range	1.0 - 100 ml	
Volume	100 ml	
Channel type	1-channel	
Operating mode	Electronic	
Materials	Housing: Polyproypylene, Membrane Filter: PTFE, Pipette Adapter: Silicone	
Power supply	100 – 240 V ±10 %, 50 – 60 Hz	
Atmospheric Pressure	79.5 – 106 kPA	
Battery	Lithium polymer	
Battery Life	2000 x 25 ml dosing cycles	
Charging time	3 h	

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.







More informations about ErgoOne® FAST Pipette Controller

Efficient pipetting

During development of the ErgoOne^{*} FAST electronic pipette controller, a high pipetting speed was recognised as an important feature. The result is convincing! The ErgoOne^{*} FAST can fill a 25 ml pipette in less than than 4 seconds!

Ergonomy meets modernity

Every aspect of ErgoOne[®] FAST has been developed with ergonomics in mind. ErgoOne[®] FAST is one of the lightest pipette controllers on the market. It is designed for comfort and balances perfectly in the hand to provide fatigue-free pipetting, even during long periods.

FAST stands for Flexible, Accurate & Precise, Safe, Transfer

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.







Accessories

PRODUCT NAMI	E	PACKAGING SIZE	ART. NO.
S)	<u>0.45 µm Membrane Filter, PTFE (Sterile), for</u> ErgoOne FAST	5 Pcs. (1 Bag × 5 Pcs.)	P7166-6800
	Sticky tape for wall mount	1 Piece (1 Pack × 1 Piece)	P7166-6701
	<u>0.2 µm Membrane Filter, PTFE (Sterile), for</u> ErgoOne FAST	5 Pcs. (1 Bag × 5 Pcs.)	P7166-6605
	Replacement Lithium Polymer Battery, 3.7 V	1 Piece (1 Bag × 1 Piece)	P7166-6501
٩	Replacement Wall mount	1 Piece (1 Box × 1 Piece)	P7166-6402
35 Q>	Replacement Power supply, 100-240 V / 50-60Hz	1 Piece (1 Box × 1 Piece)	P7166-6109
L	Replacement Aspiration cone	1 Piece (1 Box × 1 Piece)	P7166-6103
1.	<u>Replacement Pipette adapter (silicone), for</u> <u>ErgoOne FAST</u>	1 Piece (1 Box × 1 Piece)	P7166-6002
Å	ErgoOne® FAST Benchtop Support	1 Piece (1 Bag × 1 Piece)	P7166-6306

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

