



Magnetic Stirrer



Product Highlights

- Variable speed range 100 - 1500 rpm
- Stirring volume up to 3 litres
- Includes 40 mm stir bar
- Compact design
- Easy to Clean
- 2-year warranty

Product Applications

Stirring

Mixing

Buffer preparation

Dissolving elements and compounds

Cultivating microbial life

Prevent settling and caking in liquids

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab (UK) LTD
5 Tanners Drive
MK14 5BU Milton Keynes
Email: info@starlab.co.uk



General Data

Art. No.	N2400-2010
Pack Size	1 Piece (1 Box × 1 Piece)
Dimensions (W × D × H)	155 mm × 215 mm × 75 mm
Dimensions (W × D)	155 mm × 215 mm
Plate Diameter	135 mm
Weight	0.9 kg
Max. stirring volume	3 l
Power supply	100 – 240 V, 50/60 Hz
Max. power consumption	15 W
Operating temperature	4 to 40 °C
Permissible Ambient Temperature	4 – 40 °C
Max. RCF	1500 rpm
Speed Range	100 – 1,500 rpm (10 rpm steps)

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab (UK) LTD
5 Tanners Drive
MK14 5BU Milton Keynes
Email: info@starlab.co.uk



More informations about Magnetic Stirrer

Simple but effective!

Ideal for applications such as buffer preparation, this value for money magnetic stirrer has a compact footprint. Easy to use and built to last, the sturdy construction guarantees reliable stirring with the adjustable stirring speed. The unit is supplied with a 40 mm magnetic stir bar.