



### **SUPRENO® Nitrile Gloves**



#### **Product Highlights**

- Virus and micro-organism resistant
- Textured fingers
- Manufactured to the highest ISO standards

# **Product Applications**

Personal protection Occupational health and safety Sample protection Process protection

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab International GmbH







### **General Data**

Art. No. See variations  Pack Size 100 Pcs. (100 Pcs.)  Finish Textured fingers  Material Nitrile  Interior Powder-free  Color Blue  Cuff Beaded  Length 245 mm  Thickness (Cuff) 0.10 mm  Thickness (Finger) 0.18 mm  Minimum elongation before aging (%) 400  Elongation after aging (%) 400  Tonsile strength before aging (MPa) 30 MPa  Elongation after aging (MPa) 30 MPa  Elongation after aging (MPa) 10 N  Force at break before aging (N) 11 N  Shelf life 3 years  AQL 0.65  PPE 89/680/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN 374-3 / EN16523-1 In compliance, splash protection				
Finish Textured fingers  Material Nitrile  Interior Powder-free  Color Blue  Cuff Beaded  Length 245 mm  Thickness (Cuff) 0.10 mm  Thickness (Finger) 0.18 mm  Minimum elongation before aging (%) 500  Elongation after aging (%) 400  Tensile strength before aging (MPa) 30 MPa  Elongation after aging (MPa) 30 MPa  Elongation after aging (MPa) 10 N  Force at break after aging (N) 11 N  Shelf life 3 years  AQL 0.65  PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Art. No.	See variations		
Material Nitrile  Interior Powder-free  Color Blue  Cuff Beaded  Length 245 mm  Thickness (Cuff) 0.10 mm  Thickness (Finger) 0.18 mm  Minimum elongation before aging (%) 400  Elongation after aging (%) 400  Tensile strength before aging (MPa) 30 MPa  Elongation after aging (MPa) 10 N  Force at break before aging (N) 11 N  Shelf life 3 years  AQL 0.65  PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Pack Size	100 Pcs. (100 Pcs.)		
Interior Powder-free  Color Blue  Cuff Beaded  Length 245 mm  Thickness (Cuff) 0.10 mm  Thickness (Finger) 0.18 mm  Minimum elongation before aging (%) 400  Elongation after aging (%) 400  Tensile strength before aging (MPa) 30 MPa  Elongation after aging (MPa) 30 MPa  Elongation after aging (MPa) 10 N  Force at break before aging (N) 11 N  Shelf life 3 years  AQL 0.65  PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Finish	Textured fingers		
Color  Cuff Beaded  Length 245 mm  Thickness (Cuff) 0.10 mm  Thickness (Finger) 0.18 mm  Minimum elongation before aging (%) Elongation after aging (%) 400  Tensile strength before aging (MPa) Elongation after aging (MPa) 30 MPa  Elongation after aging (MPa) Force at break before aging (N) 10 N  Force at break after aging (N) 11 N  Shelf life 3 years  AQL 0.65  PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Material	Nitrile		
Cuff Beaded  Length 245 mm  Thickness (Cuff) 0.10 mm  Thickness (Finger) 0.18 mm  Minimum elongation before aging (%) 400  Elongation after aging (%) 400  Tensile strength before aging (MPa) 30 MPa  Elongation after aging (MPa) 30 MPa  Force at break before aging (N) 10 N  Force at break after aging (N) 11 N  Shelf life 3 years  AQL 0.65  PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Interior	Powder-free		
Length 245 mm  Thickness (Cuff) 0.10 mm  Thickness (Finger) 0.18 mm  Minimum elongation before aging (%) 400  Tensile strength before aging (MPa) 30 MPa  Elongation after aging (MPa) 30 MPa  Elongation after aging (MPa) 10 N  Force at break before aging (N) 11 N  Shelf life 3 years  AQL 0.65  PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Color	Blue		
Thickness (Cuff)  O.10 mm  Thickness (Finger)  O.18 mm  Minimum elongation before aging (%)  Elongation after aging (%)  Tensile strength before aging (MPa)  Elongation after aging (MPa)  30 MPa  Elongation after aging (MPa)  Force at break before aging (N)  10 N  Force at break after aging (N)  11 N  Shelf life  3 years  AQL  PPE 89/686/EEC  Personal Protective Equipment (PPE) Category III  EN 374-2  Level 3  EN374-3 / EN16523-1  In compliance, splash protection	Cuff	Beaded		
Thickness (Finger)  O.18 mm  Minimum elongation before aging (%)  Elongation after aging (%)  Tensile strength before aging (MPa)  Elongation after aging (MPa)  30 MPa  Elongation after aging (MPa)  30 MPa  Force at break before aging (N)  10 N  Force at break after aging (N)  11 N  Shelf life  3 years  AQL  0.65  PPE 89/686/EEC  Personal Protective Equipment (PPE) Category III  EN 374-2  Level 3  EN374-3 / EN16523-1  In compliance, splash protection	Length	245 mm		
Minimum elongation before aging (%)  Elongation after aging (%)  Tensile strength before aging (MPa)  30 MPa  Elongation after aging (MPa)  30 MPa  Force at break before aging (N)  10 N  Force at break after aging (N)  11 N  Shelf life  3 years  AQL  0.65  PPE 89/686/EEC  Personal Protective Equipment (PPE) Category III  EN 374-2  Level 3  EN374-3 / EN16523-1  In compliance, splash protection	Thickness (Cuff)	0.10 mm		
Elongation after aging (%)  Elongation after aging (%)  Tensile strength before aging (MPa)  30 MPa  Elongation after aging (MPa)  30 MPa  Force at break before aging (N)  10 N  Force at break after aging (N)  11 N  Shelf life  3 years  AQL  0.65  PPE 89/686/EEC  Personal Protective Equipment (PPE) Category III  EN 374-2  Level 3  EN374-3 / EN16523-1  In compliance, splash protection	Thickness (Finger)	0.18 mm		
Tensile strength before aging (MPa)  Elongation after aging (MPa)  30 MPa  Force at break before aging (N)  10 N  Force at break after aging (N)  11 N  Shelf life  3 years  AQL  0.65  PPE 89/686/EEC  Personal Protective Equipment (PPE) Category III  EN 374-2  Level 3  EN374-3 / EN16523-1  In compliance, splash protection		500		
Elongation after aging (MPa)  Force at break before aging (N)  Force at break after aging (N)  11 N  Shelf life  3 years  AQL  0.65  PPE 89/686/EEC  Personal Protective Equipment (PPE) Category III  EN 374-2  Level 3  EN374-3 / EN16523-1  In compliance, splash protection	Elongation after aging (%)	400		
Force at break before aging (N)  10 N  Force at break after aging (N)  11 N  Shelf life  3 years  AQL  0.65  PPE 89/686/EEC  Personal Protective Equipment (PPE) Category III  EN 374-2  Level 3  EN374-3 / EN16523-1  In compliance, splash protection	Tensile strength before aging (MPa)	30 MPa		
Force at break after aging (N)  11 N  Shelf life  3 years  AQL  0.65  PPE 89/686/EEC  Personal Protective Equipment (PPE) Category III  EN 374-2  Level 3  EN374-3 / EN16523-1  In compliance, splash protection	Elongation after aging (MPa)	30 MPa		
Shelf life 3 years  AQL 0.65  PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Force at break before aging (N)	ore aging (N) 10 N		
AQL 0.65  PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Force at break after aging (N)	11 N		
PPE 89/686/EEC Personal Protective Equipment (PPE) Category III  EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	Shelf life	3 years		
EN 374-2 Level 3  EN374-3 / EN16523-1 In compliance, splash protection	AQL	0.65		
EN374-3 / EN16523-1 In compliance, splash protection	PPE 89/686/EEC	Personal Protective Equipment (PPE) Category III		
	EN 374-2	Level 3		
	EN374-3 / EN16523-1	In compliance, splash protection		
ASTM F1671 In compliance	ASTM F1671	In compliance		

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab International GmbH







EN 420	Wells
PPE Regulation (EU) 2016/425	In compliance
ISO 11193-1	In compliance

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab International GmbH







### More informations about SUPRENO® Nitrile Gloves

#### Nitrile strength and durability with added security

If your need is strength and durability, SUPRENO® gloves will provide exceptional toughness in a comfortable nitrile glove. SUPRENO® gloves provide reliable protection against the hazards you work with every day. SUPRENO® gloves give the best combination of strength and durability in an all-purpose synthetic glove.

#### Recommended for use when:

- > Strength and protection are of great importance
- > Day-to-day hazards require the best combination of durability and security against specific chemicals
- > Working in environments that demand consistent grip and reliability

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab International GmbH
Neuer Höltigbaum 38
22143 Hamburg
Email: info@starlab.de







## **All Variations**

PRODUCT NA	ME	PACKAGING SIZE	ART. NO.
Subress H	SUPRENO®, Nitrile Gloves, M Size: Medium  Create PDF Data Sheet	1,000 Pcs. (10 Boxes × 100 Pcs.)	SU-INT-M
C Librery	SUPRENO®, Nitrile Gloves, L Size: Large  Create PDF Data Sheet	1,000 Pcs. (10 Boxes × 100 Pcs.)	SU-INT-L
E PRESS	SUPRENO®, Nitrile Gloves, XL Size: Extra Large  Create PDF Data Sheet	1,000 Pcs. (10 Boxes × 100 Pcs.)	SU-INT-XL

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab International GmbH

