



## Plate Centrifuge



### Product Highlights

- Holds two plates
- Two operating modes: short spin and timed
- 2,500 rpm
- Use with all 96- or 384-well plates (up to 25 mm high)
- Convenient small footprint
- Optional adapter for half plates or tubes
- 2 year warranty

## Product Applications

Quick and easy centrifugation of samples in PCR plates or microplates

Quick spin down of droplets and condensation

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

**Starlab International GmbH**  
Neuer Höltigbaum 38  
22143 Hamburg  
Email: [info@starlab.de](mailto:info@starlab.de)



## General Data

Art. No.	N2631-0100
Dimensions (W × D × H)	190 mm × 220 mm × 186 mm
Dimensions (W × D)	190 mm × 220 mm
Weight	2.6 kg
Pack Size	1 Piece (1 Box × 1 Piece)
Power supply	110 – 240 V, 50/60 Hz
Power consumption (without heating)	8 W
Max. power consumption	15 W
Timing capacity	00–099 seconds / 00–099 minutes.
Operating temperature	5°C to 40°C
Fuse	1.5 A
Noise level	51 dB (excluding timer alarm)
Permissible relative humidity	up to 80% RH at 31°C
RCF	500 × g
Rotor capacity	Two plates, any style, up to 25 mm high
Speed Range	2,500 rpm
Alarm	yes

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

**Starlab International GmbH**  
Neuer Höltigbaum 38  
22143 Hamburg  
Email: [info@starlab.de](mailto:info@starlab.de)



## More informations about Plate Centrifuge

Starlab's innovative Plate Centrifuge is tailored for the rapid and effortless centrifugation of samples in PCR plates. Use before and after thermal cycling to enhance your yield.

### CONVENIENT, TIME SAVING

Now you can stop taking plates to the big centrifuge at the other end of the lab, and having to wait for it to unlock. This plate centrifuge can sit on your bench and will spin your plates in seconds.

### FAST LOADING

Holds two standard PCR plates. Load the sealed plates vertically into the top slots.


### TWO OPERATING MODES

**SHORT:** Use for short spins. Press and hold to run at maximum speed. The [timer](#) will count up. Release the button to stop centrifuging.

**TIMER:** For longer centrifugation or hands-free operation, set a duration. Centrifuging will stop when the set time has elapsed.



## Accessories

PRODUCT NAME	PACKAGING SIZE	ART. NO.
 <a href="#">Adapter for 1/2 plates, strips and tubes</a>	2 Piece (1 Box × 2 Piece)	N2631-0018

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

**Starlab International GmbH**  
Neuer Höltigbaum 38  
22143 Hamburg  
Email: [info@starlab.de](mailto:info@starlab.de)