



Rotator Mixer Multi 1



Product Highlights

- Controlled sample inverting
- Programmable
- Three different motions
- Variable speed and timer
- Low profile and small footprint
- LCD display
- Capacity of up to 26 sample tubes
- 2-year warranty

Product Applications

Sample Preparation

Handling of cell suspension

Incubation

Extraction procedures

Gel washing and precipitations

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab International GmbH
Neuer Höltingbaum 38
22143 Hamburg
Email: info@starlab.de



General Data

Art. No.	N2400-5000
Pack Size	1 Piece (1 Box × 1 Piece)
Dimensions (W × D × H)	365 mm × 195 mm × 155 mm
Dimensions (W × D)	365 mm × 195 mm
Weight	1.8 kg
Timing capacity	Auto switch-off: 1 minute - 24 hours. Vertical or Reciprocal Mode: 0 - 250 seconds, or non-stop. Vibration mode: 0 - 5 seconds
Operating temperature	4 to 40 °C
Permissible Ambient Temperature	4 – 40 °C
Max. Load	0.5 kg
Output	1.25 A
Speed Range	1-100 rpm (increment 1 rpm)

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab International GmbH
Neuer Höltingbaum 38
22143 Hamburg
Email: info@starlab.de



More informations about Rotator Mixer Multi 1

Mix it up!



Compact and multifunctional, the programmable Rotator Mixer Multi 1 provides thorough mixing of microtubes with consistent results. The rotator is designed for mixing applications including cell suspensions, incubations, extraction procedures, gel washing and precipitations.

The three different motions – vertical rotation, reciprocal motion and vibration – can be used separately or combined, as well as variable speed and timer functions.

Supplied with a standard platform for 26 tubes up to 15 mm diameter (eg. 1.5 ml, 2.0 ml and 15 ml tubes), STARLAB's Rotator Mixer is a practical aid for your daily mixing tasks. An optional platform, for five tubes up to 30 mm diameter (eg. 50 ml tubes) and 12 tubes up to 15 mm diameter, is available separately.



Accessories

PRODUCT NAME		PACKAGING SIZE	ART. NO.
	Platform for 26 tubes up to 15mm diameter	1 Piece (1 Box × 1 Piece)	N2400-5104
	Platform for 5x50ml + 12x1.5-15ml tubes	1 Piece (1 Box × 1 Piece)	N2400-5103

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

Starlab International GmbH
Neuer Höltingbaum 38
22143 Hamburg
Email: info@starlab.de